



The super resistant and compact cylindrical dripline



Product description

Mini® is a low density polyethylene dripline characterized by a short cylindrical dripper with self-cleaning turbulent flow. The labyrinth design with wide water passages reduces the risk of clogging. The 4 dispensing holes in a specular position avoid percolation on the pipe ensuring a more balanced distribution of water over the entire irrigated surface.

Mini® is a dripline with a short and compact emitter with incredible field performance in fact it is extremely durable even in the most difficult conditions.

Product range

| | |
|--|---|
| | 16 |
| | 30 - 32 - 35 - 40 - 44 |
| | 0,76 - 0,81 - 0,89 - 1,02 - 1,12 |
| | 1,6 - 2,2 - 4,2 |
| | 15 - 20 - 23 - 25 - 30 - 33 - 40 - 50 - 60 - 70 80 - 100 - 120 - 150 |

On request:

- Available in brown and white color
- Availability of alternating pitch emitters

Table in nominal values

Dripper features

- Short and compact cylindrical dripper;
- Turbulent flow;
- Labyrinth with self-cleaning design and large water passages;
- Integrated filter reduces the passage of impurities;
- Low sensitivity to pressure;
- Low coefficient of technological variation;

Recommended applications

Surface application is recommended, on level ground where pressure compensation is not required.



Crops

Mini® is suitable for open field or greenhouse applications in tree crops and multi-seasonal cycles such as oranges, lemons, grapes, apples, pears, almonds, olives, kiwis, hazelnuts and others.



Advantages

- Reliable operation and longer life;
- Better homogeneity of the irrigated surface thanks to the 4 holes placed in a specular way;
- Reduction of percolation on the pipe;
- Excellent emission uniformity along the entire length of the line;
- High resistance to UV rays and fertilizers used in agriculture;
- Complete emptying at the end of the irrigation cycle with consequent lower risk of blockage;
- Simplicity and speed of installation thanks to the specular position of the dispensing holes;
- Very little maintenance required.

Maximum length of recommended lines, in metres, with emission uniformity (E.U.) of 85%

| DIAMETER Ø - mm | FLOW RATE 1 bar | SPACING cm | | | | | | | | | | | | SLOPE | |
|--------------------|--------------------|---------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------|----|
| | | 15 | 20 | 25 | 30 | 33 | 40 | 50 | 60 | 70 | 80 | 100 | 120 | | |
| 16 | 1,6 | 53 | 67 | 78 | 86 | 91 | 98 | 111 | 118 | 125 | 131 | 140 | 145 | 151 | -1 |
| | | 59 | 78 | 91 | 103 | 110 | 125 | 145 | 163 | 179 | 196 | 228 | 256 | 296 | 0 |
| | | 65 | 87 | 104 | 120 | 131 | 150 | 179 | 208 | 235 | 262 | 320 | 372 | 453 | 1 |
| | 2,2 | 42 | 54 | 62 | 69 | 73 | 79 | 89 | 95 | 101 | 105 | 112 | 116 | 121 | -1 |
| | | 47 | 63 | 73 | 83 | 88 | 100 | 117 | 131 | 144 | 157 | 182 | 204 | 237 | 0 |
| | | 52 | 70 | 83 | 96 | 105 | 120 | 144 | 167 | 189 | 210 | 255 | 297 | 363 | 1 |
| | 4,2 | 28 | 36 | 41 | 45 | 48 | 52 | 58 | 62 | 66 | 69 | 74 | 76 | 79 | -1 |
| | | 31 | 42 | 48 | 54 | 58 | 66 | 76 | 86 | 94 | 104 | 120 | 134 | 156 | 0 |
| | | 35 | 46 | 55 | 63 | 69 | 79 | 94 | 109 | 124 | 139 | 168 | 195 | 239 | 1 |

The values of the lines in meters are indicative

Specifications Packaging - Standard rolls

| DIAMETER Ø - mm | THICKNESS mil | Roll length m | Rolls / Container-Truck | | | Meters / Container | | | Meters / Truck | |
|--------------------|------------------|------------------|-------------------------|--------|-------|--------------------|---------|--|----------------|--|
| | | | 20Ft | 40FtHC | Truck | 20Ft | 40FtHC | | | |
| 16 | 35 | 400 | 170 | 400 | 500 | 68000 | 160.000 | | 200.000 | |
| | 44 | | | | | | | | | |

Specifications Packaging - Small rolls

| DIAMETER Ø - mm | THICKNESS mil | Roll length m | Rolls / pallets | Rolls / Container-Truck | | | Meters / Container | | | Meters / Truck | |
|--------------------|------------------|------------------|-----------------|-------------------------|--------|-------|--------------------|--------|---------|----------------|--|
| | | | | 20Ft | 40FtHC | Truck | 20Ft | 40FtHC | | | |
| 16 | 35 - 44 | 35 - 44 | 25 | 100 | 1.000 | 2.000 | 2.200 | 25.000 | 50.000 | 55.000 | |
| | | | 50 | 88 | 880 | 1.760 | 1.936 | 44.000 | 88.000 | 96.800 | |
| | | | 100 | 48 | 480 | 960 | 1.056 | 48.000 | 96.000 | 105.300 | |
| | | | 200 | 28 | 280 | 560 | 616 | 56.000 | 112.000 | 123.200 | |

Soaplast reserves the right to make to its catalogs and products, at any time and without notice, any modifications which, in its unquestionable judgement, it deems convenient for production purposes and/or useful for improving their quality, functionality and performance.

Price tables

Standard rolls for agriculture

| DIAMETER Ø | THICKNESS | SPACING (cm) | | | | | | | | | | | | | | | | |
|---------------|-----------|--------------|-------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | 15 | 20 | 25 | 30 | 33 | 35 | 40 | 50 | 60 | 70 | 75 | 80 | 90 | 100 | 110 | 125 | 150 |
| | | mil | mm | PRICE €/m | | | | | | | | | | | | | | |
| 16 | 35 | 0,90 | 0,255 | 0,208 | 0,182 | 0,177 | 0,175 | 0,173 | 0,170 | 0,166 | 0,164 | 0,162 | 0,161 | 0,160 | 0,159 | 0,158 | 0,158 | 0,158 |
| | 44 | 1,10 | 0,272 | 0,226 | 0,200 | 0,195 | 0,193 | 0,191 | 0,188 | 0,184 | 0,181 | 0,180 | 0,179 | 0,178 | 0,177 | 0,176 | 0,176 | 0,176 |

Reduced rolls for gardening

| DIAMETER Ø | THICKNESS | | LENGTH ROLL | SPACING (cm) | | | | | | | | |
|---------------|-----------|------|----------------|--------------|-------|-------|-------|-------|-------|-------|-----------|-------|
| | | | | 15 | 20 | 25 | 30 | 33 | 35 | 40 | PRICE €/m | |
| | mil | mm | | 25 | 0,450 | 0,371 | 0,350 | 0,337 | 0,331 | 0,327 | 0,320 | |
| 16 | 35 | 0,90 | 25 | 50 | 0,441 | 0,362 | 0,341 | 0,328 | 0,322 | 0,318 | 0,311 | 0,245 |
| | | | | 100 | 0,375 | 0,296 | 0,275 | 0,262 | 0,256 | 0,252 | 0,245 | |
| | | | 44 | 200 | 0,340 | 0,261 | 0,240 | 0,227 | 0,221 | 0,217 | 0,210 | 0,260 |
| | | | | 25 | 0,471 | 0,386 | 0,366 | 0,352 | 0,346 | 0,343 | 0,335 | |
| | 44 | 1,10 | 50 | 100 | 0,462 | 0,377 | 0,357 | 0,343 | 0,337 | 0,334 | 0,326 | 0,260 |
| | | | | 200 | 0,396 | 0,311 | 0,291 | 0,277 | 0,271 | 0,268 | 0,260 | |
| | | | 25 | 50 | 0,361 | 0,276 | 0,256 | 0,242 | 0,236 | 0,233 | 0,225 | 0,260 |
| | | | | 100 | 0,396 | 0,311 | 0,291 | 0,277 | 0,271 | 0,268 | 0,260 | |

Available in brown color with a supplement of €0.047m